

# CF VI CENTRIFUGE

TRANSPARENT LID WITH  
SAFETY INTERLOCK

SEALED EASY TO  
REMOVE DOME  
SHIELDS COME  
STANDARD

SIMPLE  
INTUITIVE  
CONTROL

COMPACT  
LIGHT WEIGHT  
LOW PROFILE



The rugged CF-VI centrifuge is designed for all benchtop applications. Its proven mechanics combined with modern digital control, intuitive operation, compact dimensions and versatility make it the natural choice for both small and large facilities.

Durability, ease of use, small size and universal application make it an easy winner.

Nothing else comes close.

**CYGNUS**<sup>LLC</sup> 

Technology as Passion

510 East 41st Street, Paterson, NJ 07504  
phone 973-523-0668  
fax 973-523-0375  
email info@cygnusnj.com  
www.cygnusnj.com

## SPECIFICATIONS

The CF-VI Centrifuge conforms to all UL, FDA, OSHA and VDA (EU) regulations in effect on date of manufacture. It is ETL-listed against UL standard 61010-1.

Power requirements: 115VAC ÷ 220VAC / 50Hz ÷ 60Hz

Rated Max Speed: 3000RPM

Relative Centrifugal Force: Standard Blood mode - 1600G, 10min  
Dual mode available - Blood 1600G/10min and Urine 1100G/6min

Any other combination of force and cycle duration can be programmed per customer specification.

Cord: UL listed, 6ft (1.8m), strain-relieved, grounded cord and plug

Dimensions: 11 x 11 inches (28x28cm)  
9.25 inches high (23.5cm)

Number of places: 6

Angle of rotation: 49°

Weight: 7lbs (3.2KG)

Shipping Weight: 10lbs (4.5KG)

## ACCESSORIES

Each CF-VI centrifuge comes standard with a full set of dome shields and tube adapters



**Intertek**  
4000919



**Intertek**

